



Asked. . . Answered.

utility/power/telcom

Compression Splices, Non Tension, 8Ga-500MCM

ASK Part No.	CONDUCTOR A	CONDUCTOR B	Barrel Config	Finish	Conductor "A" Barrel I.D.	Conductor "B" Barrel I.D.	Barrel O.D. "C"	Overall Length "E" Tol	Color Code	# Crimps	Burndy Die	Homac Die Code
AS6X	6 SOLID 8 STR	6 SOLID 8 STR	Standard	TIN/CLRCD	0.188	0.188	0.625	2.00	GREEN / GREEN	2	BG,243	TU
AS4X-8X	4 SOLID 5&6 STR, ACSR 6-6/1	SOLID 8 10 STR	Standard	TIN/CLRCD	0.214	0.170	0.625	2.00	BLUE / BROWN	2	BG,243	TU
AS4X-6X	4 SOLID 5&6 STR, ACSR 6-6/1	6 SOLID 8 STR	Standard	TIN/CLRCD	0.214	0.181	0.625	2.00	BLUE / GREEN	2	BG,243	TU
AS4X	4 SOLID 5&6 STR, ACSR 6-6/1	4 SOLID 5&6 STR, ACSR 6-6/1	Standard	TIN/CLRCD	0.214	0.214	0.625	2.00	BLUE / BLUE	2	BG,243	TU
AS2X-6X	2 SOLID 3&4 STR, ACSR 4-6/1 7/1	6 SOLID 8 STR	Standard	TIN/CLRCD	0.285	0.181	0.625	2.00	ORANGE / GREEN	2	BG,243	TU
AS2X-4X	2 SOLID 3&4 STR, ACSR 4-6/1 7/1	4 SOLID 5&6 STR, ACSR 6-6/1	Standard	TIN/CLRCD	0.285	0.214	0.625	2.00	ORANGE / BLUE	2	BG,243	TU
AS2X	2 SOLID 3&4 STR, ACSR 4-6/1 7/1	2 SOLID 3&4 STR, ACSR 4-6/1 7/1	Standard	TIN/CLRCD	0.285	0.285	0.625	2.00	ORANGE / ORANGE	2	BG,243	TU
AS2-8X	1 SOLID 1&2 STR, ACSR 1-6/1, 7/1	8 SOLID 10 STR	Standard	TIN/CLRCD	0.360	0.170	0.625	2.00	RED / BROWN	2	BG,243	TU
AS2-6X	1 SOLID 1&2 STR, ACSR 1-6/1, 7/1	6 SOLID 8 STR	Standard	TIN/CLRCD	0.360	0.181	0.625	2.00	RED / GREEN	2	BG,243	TU
AS2-4X	1 SOLID 1&2 STR, ACSR 1-6/1, 7/1	4 SOLID 5&6 STR, ACSR 6-6/1	Standard	TIN/CLRCD	0.360	0.214	0.625	2.00	RED / BLUE	2	BG,243	TU
AS2-2X	1 SOLID 1&2 STR, ACSR 1-6/1, 7/1	2 SOLID 3&4 STR, ACSR 4-6/1 7/1	Standard	TIN/CLRCD	0.360	0.285	0.625	2.00	RED / ORANGE	2	BG,243	TU
AS2	1 SOLID 1&2 STR, ACSR 1-6/1, 7/1	1 SOLID 1&2 STR, ACSR 1-6/1, 7/1	Standard	TIN/CLRCD	0.360	0.360	0.625	2.00	RED / RED	2	BG,243	TU
AS10-4X	1/0 STR, ACSR 1/0-6/1	4 SOLID 5&6 STR, ACSR 6-6/1	Standard	TIN/CLRCD	0.410	0.214	0.625	2.00	YELLOW / BLUE	2	BG,243	TU
AS10-2X	1/0 STR, ACSR 1/0-6/1	2 SOLID 3&4 STR, ACSR 4-6/1 7/1	Standard	TIN/CLRCD	0.410	0.285	0.625	2.00	YELLOW / ORANGE	2	BG,243	TU
AS10-2	1/0 STR, ACSR 1/0-6/1	1 SOLID 1&2 STR, ACSR 1-6/1, 7/1	Standard	TIN/CLRCD	0.410	0.360	0.625	2.00	YELLOW / RED	2	BG,243	TU
AS10	1/0 STR, ACSR 1/0-6/1	1/0 STR, ACSR 1/0-6/1	Standard	TIN/CLRCD	0.410	0.410	0.625	2.00	YELLOW / YELLOW	2	BG,243	TU
AS20-2	3/0 SOLID, 2/0 STR, ACSR 2/0	1 SOLID 1&2 STR, ACSR 2	Standard	TIN/CLRCD	0.460	0.302	0.906	4.00	GREY / RED	6	K840 / 249	TX
AS20-10	3/0 SOLID, 2/0 STR, ACSR 2/0	1/0 & 2/0 SOLID, 1/0 STR, ACSR 1/0	Standard	TIN/CLRCD	0.460	0.410	0.906	4.00	GREY / YELLOW	6	K840 / 249	TX
AS20	3/0 SOLID, 2/0 STR, ACSR 2/0	3/0 SOLID, 2/0 STR, ACSR 2/0	Standard	TIN/CLRCD	0.460	0.460	0.906	4.00	GREY / GREY	6	K840 / 249	TX
AS30-2	4/0 SOLID, 3/0 STR, ACSR 3/0	1 SOLID 1&2 STR, ACSR 2	Standard	TIN/CLRCD	0.510	0.302	0.906	4.00	BLACK / RED	6	K840 / 249	TX
AS30-10	4/0 SOLID, 3/0 STR, ACSR 3/0	1/0 & 2/0 SOLID, 1/0 STR, ACSR 1/0	Standard	TIN/CLRCD	0.510	0.410	0.906	4.00	BLACK / YELLOW	6	K840 / 249	TX
AS30-20	4/0 SOLID, 3/0 STR, ACSR 3/0	3/0 SOLID, 2/0 STR, ACSR 2/0	Standard	TIN/CLRCD	0.510	0.460	0.906	4.00	BLACK / BLACK	6	K840 / 249	TX
AS40-4	4/0 STR, ACSR 4/0	2 SOLID 3&4 STR, ACSR 4	Standard	TIN/CLRCD	0.560	0.285	0.906	4.00	PINK / ORANGE	6	K840 / 249	TX
AS40-2	4/0 STR, ACSR 4/0	1 SOLID 1&2 STR, ACSR 2	Standard	TIN/CLRCD	0.560	0.302	0.906	4.00	PINK / RED	6	K840 / 249	TX
AS40-10	4/0 STR, ACSR 4/0	1/0 & 2/0 SOLID, 1/0 STR, ACSR 1/0	Standard	TIN/CLRCD	0.560	0.410	0.906	4.00	PINK / YELLOW	6	K840 / 249	TX
AS40-20	4/0 STR, ACSR 4/0	3/0 SOLID, 2/0 STR, ACSR 2/0	Standard	TIN/CLRCD	0.560	0.460	0.906	4.00	PINK / GREY	6	K840 / 249	TX
AS40-30	4/0 STR, ACSR 4/0	4/0 SOLID, 3/0 STR, ACSR 3/0	Standard	TIN/CLRCD	0.560	0.510	0.906	4.00	PINK / BLACK	6	K840 / 249	TX
AS40	4/0 STR, ACSR 4/0	4/0 STR, ACSR 4/0	Standard	TIN/CLRCD	0.560	0.560	0.906	4.00	PINK / PINK	6	K840 / 249	TX
AS350-10	397.5 TO 400 SOLID, 300 TO 350 STR, ACSR 336.4 (18/1)	1/0 & 2/0 SOLID, 1/0 STR, ACSR 1/0	Standard	TIN/CLRCD	0.700	0.410	0.906	4.00	BROWN / YELLOW	6	K840 / 249	TX
AS350-40	397.5 TO 400 SOLID, 300 TO 350 STR, ACSR 336.4 (18/1)	4/0 STR, ACSR 4/0	Standard	TIN/CLRCD	0.700	0.560	0.906	4.00	BROWN / PINK	6	K840 / 249	TX
AS350	397.5 TO 400 SOLID, 300 TO 350 STR, ACSR 336.4 (18/1)	397.5 TO 400 SOLID, 300 TO 350 STR, ACSR 336.4 (18/1)	Standard	TIN/CLRCD	0.700	0.700	0.906	4.00	BROWN / BROWN	6	K840 / 249	TX
AS500	400-500 STR, ACSR 397.5 (18/1), 477(18/1)	400-500 STR, ACSR 397.5 (18/1), 477(18/1)	Standard	TIN/CLRCD	0.875	0.875	1.187	7.60	NONE	6	655	96H